

PRODUCT PROFILE

PowerFlex® 4 AND PowerFlex® 40 AC DRIVES

Providing users with powerful motor speed control in a compact, space saving design, the Allen-Bradley® PowerFlex 4 and PowerFlex 40 AC drives are the smallest and most cost effective members of the PowerFlex® family of drives. Ideal for machine level speed control, these products provide the application versatility to meet the demands of global OEMs and end users who require flexibility, space savings and ease of use. The PowerFlex 4 and PowerFlex 40 AC drives have commonality in three key areas:

Flexible Packaging and Mounting Options

- Installation can be a virtual snap using the DIN rail mounting feature on A and B frame drives.
- Flange mount drives are available to reduce overall enclosure size.
- Zero Stacking™ is allowable for ambient temperatures up to 40°C, saving valuable panel space. 50°C ambient temperatures are permitted with minimal spacing between drives.

Easy to Start up and Operate

- Integral keypad features a 4 digit display and 10 additional LED indicators providing intuitive control.
- The keypad, control keys, and local potentiometer are active out of the box, simplifying start up.
- The 10 most commonly programmed parameters are grouped together for fast and easy start up.

Versatile Programming and Network Solutions

- Integral RS485 communications enable the drives to be used in a multi-drop network configuration. A serial converter module provides connectivity to any controller that has the ability to initiate DF1 messaging.
- DriveExplorer™ and DriveTools™ SP software can be used to program, monitor and control the drives.
- A NEMA 4X remote and NEMA 1 handheld LCD keypad provide additional programming and control flexibility, both featuring the popular CopyCat function.

PROVIDE OPTIMIZED SIMPLICITY



1

PowerFlex 4 AC Drive 0.2 to 3.7 kW; 0.25 to 5 hp 120, 240, 480 V

2

PowerFlex 40 AC Drive, 0.4 to 11 kW; 0.5 to 15 hp 120, 240, 480, 600 V (Product shown with DeviceNet option)

3

PowerFlex 4 and 40 Flange Mount Drives

PowerFlex 4 AC Drive

Designed with simplicity and space savings in mind, the PowerFlex 4 is:

- Ideal for applications with limited panel space
- An economical replacement for electromechanical devices or DC solutions

PowerFlex 40 AC Drive

The PowerFlex 40 AC drive shares all the same features and functionality of the PowerFlex 4 AC drive. In addition the PowerFlex 40 AC drive features sensorless vector control and has additional I/O capability. Designed with application versatility and robust performance in mind, the PowerFlex 40 AC drives also features:


- 0-10V or 4-20mA (10-bit) analog output for feedback or as reference for other drives
- Timer, counter and StepLogic™ functions can reduce hardware design cost, simplifying control schemes
- Two analog input channels, including PID capability, offer enhanced application flexibility
- Integral communication option cards such as DeviceNet™, EtherNet/IP™, PROFIBUS™ DP and ControlNet™ can improve machine performance

PowerFlex 40 Packaged Drives Program

The PowerFlex 40 Packaged Drives Program simplifies installation and start up by allowing users to order drive packages that combine operator interface, control, communications and power options in pre-packaged assemblies. Offering a number of commonly requested pre-engineered options, as well as more complex custom-engineered combinations, this program provides a wide range of motor control options.

NOW WE'RE TALKING... LOW COST COMMUNICATIONS!

SIMPLE RS485 SOLUTIONS



- Controls and monitors from a PC using DriveExplorer™ or DriveTools™ SP software
- Requires use of Serial Converter Module (SCM)



- Simple network control with any logic controller using DF1 messaging
- Requires use of Serial Converter Module (SCM)




- Compatible with any device that acts as RTU Master
- Drive supports standard 03 and 06 RTU commands

ADVANCED NETWORK SOLUTIONS



- Multi-drive solution using a single PowerFlex 40 DeviceNet option
- Significantly reduces node count and system cost




- Network configuration using PowerFlex 40 drives with DeviceNet option cards
- Provides highest performance and most flexible configuration capabilities

AND, EVEN LOWER COST MACHINE LEVEL CONTROL.

Timer and Counter Functions

- Digital inputs control digital outputs based on timer or counter function



Ideal for:
Mixers
Fillers
Shrink-wrap machines

Basic Logic Functions

- Digital inputs control digital outputs based on Boolean logic
- AND and OR logic inputs provide application flexibility



Ideal for:
Packaging machines
Conveyors
Palletizers

StepLogic™ Function

- Logic controlled steps using preset speed settings
- Each step can be programmed to:
 - Step based on digital input status including AND, OR and NOT logic
 - Step based on specific time
 - Control speed, direction and accel/decel rate
 - Control the status of an output
- Make deterministic jumps



Ideal for:
Positioning
Shuttle transfer cars
Machine tool
Batch process

	PowerFlex 4	PowerFlex 40																																	
Operator Interface	Integral keypad with a 4 digit display, 10 additional LED indicators and local potentiometer, optional Remote Human Interface Modules (HIM)																																		
Standards	UL, C-Tick, CE, EMC EN61800-3, Low Voltage EN60204-1/EN50178																																		
Input Specifications	1 Phase Voltage: 100 - 120V / 200 - 240V 3-Phase Voltage: 200 - 240V / 380 - 480V Frequency: 47 to 63 Hz Logic Control Ride Through: >0.5 seconds, 2 seconds typical Voltage: Adjustable from 0V to rated motor voltage Intermittent Current: 150% for 60 seconds	1 Phase Voltage: 100 - 120V / 200 - 240V 3-Phase Voltage: 200 - 240V / 380 - 480V / 480 - 600V Frequency: 47 to 63 Hz Logic Control Ride Through: >0.5 seconds, 2 seconds typical Voltage: Adjustable from 0V to rated motor voltage Intermittent Current: 150% for 60 seconds																																	
Output Specifications	Voltage: Adjustable from 0V to rated motor voltage Intermittent Current: 150% for 60 seconds																																		
Enclosure and Ambient Operating Temperature	Open Type / IP20: -10° to 50° C (14° - 122°F) NEMA Type 1 / IP30: -10° to 40° C (14° - 104°F) with optional conduit box kit																																		
Frequency Range	0 - 240 Hz	0 - 400 Hz																																	
Control	24V sink or source control 3 dedicated inputs for start, stop and reverse 2 programmable inputs for functions such as preset speed, jog, etc. 0 - 10V or 4 - 20mA input 1 programmable form C relay output	24V sink or source control 3 dedicated inputs for start, stop and reverse 4 programmable inputs for functions such as preset speeds, jog, etc. ± 10V (bipolar), 0 - 10V and 4 - 20 mA 1 programmable form C relay output 1 analog output (0 - 10V or 4 - 20mA) 2 programmable opto outputs																																	
Dynamic Braking	7th IGBT included on all ratings (except no brake drives)	7th IGBT included on all ratings																																	
Carrier Frequency	2-16 kHz. The drive rating is based on 4 kHz																																		
Frequency Accuracy	Digital input within + 0.05% of set frequency Analog input within 0.5% of maximum output frequency																																		
Ratings	<table border="1"> <thead> <tr> <th>Voltage Class</th> <th>A Frame Ratings</th> <th>B Frame Ratings</th> </tr> </thead> <tbody> <tr> <td>100-120V, 1Ø</td> <td>0.2-0.37 kW (0.25-0.5 HP)</td> <td>0.75-1.1 kW (1-1.5 HP)</td> </tr> <tr> <td>200-240V, 1Ø</td> <td>0.2-0.75 kW (0.25-1 HP)</td> <td>1.5-2.2 kW (2-3 HP)</td> </tr> <tr> <td>200-240V, 3Ø</td> <td>0.2-1.5 kW (0.25-2 HP)</td> <td>2.2-3.7 kW (3-5 HP)</td> </tr> <tr> <td>380-480V, 3Ø</td> <td>0.37-1.5 kW (0.5-2 HP)</td> <td>2.2-3.7 kW (3-5 HP)</td> </tr> </tbody> </table>	Voltage Class	A Frame Ratings	B Frame Ratings	100-120V, 1Ø	0.2-0.37 kW (0.25-0.5 HP)	0.75-1.1 kW (1-1.5 HP)	200-240V, 1Ø	0.2-0.75 kW (0.25-1 HP)	1.5-2.2 kW (2-3 HP)	200-240V, 3Ø	0.2-1.5 kW (0.25-2 HP)	2.2-3.7 kW (3-5 HP)	380-480V, 3Ø	0.37-1.5 kW (0.5-2 HP)	2.2-3.7 kW (3-5 HP)	<table border="1"> <thead> <tr> <th>Voltage Class</th> <th>B Frame Ratings</th> <th>C Frame Ratings</th> </tr> </thead> <tbody> <tr> <td>100-120V, 1Ø</td> <td>0.4-1.1 kW (0.5-1.5 HP)</td> <td></td> </tr> <tr> <td>200-240V, 1Ø</td> <td>0.4-1.5 kW (0.5-2 HP)</td> <td>2.2 kW (3 HP)</td> </tr> <tr> <td>200-240V, 3Ø</td> <td>0.4-3.7 kW (0.5-5 HP)</td> <td>5.5-7.5 kW (7.5-10 HP)</td> </tr> <tr> <td>380-480V, 3Ø</td> <td>0.4-4.0 kW (0.5-5 HP)</td> <td>5.5-11 kW (7.5-15 HP)</td> </tr> <tr> <td>480-600V, 3Ø</td> <td>0.75-4.0 kW (1-5 HP)</td> <td>5.5-11 kW (7.5-15 HP)</td> </tr> </tbody> </table>	Voltage Class	B Frame Ratings	C Frame Ratings	100-120V, 1Ø	0.4-1.1 kW (0.5-1.5 HP)		200-240V, 1Ø	0.4-1.5 kW (0.5-2 HP)	2.2 kW (3 HP)	200-240V, 3Ø	0.4-3.7 kW (0.5-5 HP)	5.5-7.5 kW (7.5-10 HP)	380-480V, 3Ø	0.4-4.0 kW (0.5-5 HP)	5.5-11 kW (7.5-15 HP)	480-600V, 3Ø	0.75-4.0 kW (1-5 HP)	5.5-11 kW (7.5-15 HP)
Voltage Class	A Frame Ratings	B Frame Ratings																																	
100-120V, 1Ø	0.2-0.37 kW (0.25-0.5 HP)	0.75-1.1 kW (1-1.5 HP)																																	
200-240V, 1Ø	0.2-0.75 kW (0.25-1 HP)	1.5-2.2 kW (2-3 HP)																																	
200-240V, 3Ø	0.2-1.5 kW (0.25-2 HP)	2.2-3.7 kW (3-5 HP)																																	
380-480V, 3Ø	0.37-1.5 kW (0.5-2 HP)	2.2-3.7 kW (3-5 HP)																																	
Voltage Class	B Frame Ratings	C Frame Ratings																																	
100-120V, 1Ø	0.4-1.1 kW (0.5-1.5 HP)																																		
200-240V, 1Ø	0.4-1.5 kW (0.5-2 HP)	2.2 kW (3 HP)																																	
200-240V, 3Ø	0.4-3.7 kW (0.5-5 HP)	5.5-7.5 kW (7.5-10 HP)																																	
380-480V, 3Ø	0.4-4.0 kW (0.5-5 HP)	5.5-11 kW (7.5-15 HP)																																	
480-600V, 3Ø	0.75-4.0 kW (1-5 HP)	5.5-11 kW (7.5-15 HP)																																	
Dimensions mm (inches)	A Frame: 152 (5.98) H X 80 (3.15) W X 136 (5.35) D B Frame: 180 (7.09) H X 100 (3.94) W X 136 (5.35) D	B Frame: 180 (7.09) H X 100 (3.94) W X 136 (5.35) D C Frame: 260 (10.2) H X 130 (5.1) W X 180 (7.1) D																																	
Additional Functionality	Sensorless vector control Process PID StepLogic™ functions (relays and timers) Integral communication options: <ul style="list-style-type: none"> - DeviceNet - EtherNet/IP - PROFIBUS DP - ControlNet PTC input compatible																																		
Additional Accessories	EMC line filters Line reactors Dynamic brake resistors DSI cable accessories																																		

PowerFlex, Zero Stacking, DriveExplorer, StepLogic and DriveTools SP are trademarks of Rockwell Automation. Trademarks not belonging to Rockwell Automation are property of their respective companies.

www.rockwellautomation.com

Motors, Drives and Power Transmission Solutions

Americas: Rockwell Automation, 6040 Ponders Court, Greenville, SC 29615-4617 USA, Tel: (1) 864.297.4800, Fax: (1) 864.281.2433

Europe/Middle East/Africa: Rockwell Automation, Herman-Heinrich-Gossen-Strasse 3, 50858 Köln, Germany, Tel: 49 (0) 2234 379410, Fax: 49 (0) 2234 3794164

Asia Pacific: Rockwell Automation, 55 Newton Road, #11-01/02 Revenue House, Singapore 307987, Tel: (65) 6356 9077, Fax: (65) 6356 9011